

## Product model: M8106T-5G-GL

### 5G WIFI6 Vehicle / Bus Router

## 1 Brief Introduction

M8106T-5G-GL is a 5G WIFI6 vehicle cellular router, which can access the Internet through 5G mobile communication dial-up or 1000Mbps WAN port, and then share the Internet network through wireless WiFi 6 and 1000Mbps wired LAN.

Related standard specifications:

- 1)USB3.0/USB2.0 bus standard
- 2)PCI- Express bus standard
- 3)SIM/USIM interface standard
- 4)IEEE802.11n/g/b/a/ac/ax
- 5)IEEE802.3/802.3u/802.ab
- 6)PCI Express M.2 Specification Rev1.1

### 5G Frequencies Supported:

NSA: n1/n2/n3/n5/n7/n8/n12/n13/n14/n20/n25/n26/n28/n29/n30/n38/n40/n41/n48/n66/n71/n75/n76/n77/n78/n79

SA: n1/n2/n3/n5/n7/n8/n12/n13/n14/n20/n25/n26/n28/n29/n30/n38/n40/n41/n48/n66/n71/n75/n76/n77/n78/n79

LTE-FDD B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B18/B19/B20/B25/B26/B28/B29/B30/B32/B66/B71

LTE-TDD B34/B38/B39/B40/B41/B42/B43/B48

LAA: B46

WCDMA: B1/2/4/5/8/19

## 2 Product image (Product Size: 162x128x43mm)



### 3 Product main features

- 1) Using MT7981B solution, ARM Cortex-A53 dual-core CPU, main frequency up to 1.3GHZ
- 2) Adopt independent WIFI6 chip, MT7976CN, the speed is up to 3000Mbps
- 3) High-speed 1GB DDR4, with 128MB SPI NAND Flash
- 4) 1WAN+4LAN 1000M adaptive network port, support automatic flip (Auto MDI/MDIX)..
- 5) Support "one-key flashing mode", that is, long press the reset button to enter the rescue flashing mode...
- 6) Built-in 2 M.2/Mini-PCIE standard interfaces (choose one of the two), which can be used to connect to 5G mobile communication modules
- 7) External standard Nano SIM card (small card) interface and built-in eSIM (QFN-8 6mmx5mm) card interface, support SIM/USIM card
- 8) External high-gain WIFI antenna, 360-degree wireless signal without dead angle

### 4 Hardware function

#### 4.1 Hardware Interface Introduction

RJ45 ports	1*WAN port, 1000Mbps/2.5GB supports automatic flip (Auto MDI/MDIX) Conforms to IEEE 802.3/802.3u/802.ab
	4* LAN port, 1000Mbps supports automatic flip (Auto MDI/MDIX) Conforms to IEEE 802.3/802.3u/802.ab
power interface	DC5.5*2.1MM, support wide power range 12V~32V
USB port	USB3.0
Button	1 reset button, 1 MESH button
4G/5G interface	1 *M.2 ports
Antennas	2 *detachable omnidirectional 5dbi 2.4G antennas
	2 *detachable omnidirectional 5dbi 5.8G antennas
	4*detachable omnidirectional 5dbi 5G mobile communication antennas

## 4.2 Indicator light function introduction

MESH LED	<ol style="list-style-type: none"> <li>1. The red light is on during the boot process, when the boot is complete, the red light is off and the green light is on</li> <li>2. Press the mesh button to enter the mesh pairing state, the green light flashes once a second, and the other lights are off</li> <li>3. The network of the main device is normal, and the green light and blue light are on at the same time (cyan)</li> <li>4. The MESH connection from the device is successful. If the distance is far away, the green light and red light will be on at the same time (orange), and the green light and blue light will be on at the same time (cyan) if the distance is suitable.</li> </ol>
5G LED	The 5G network is always on, and flashes when there is data communication

## 4.3 Hardware Platform Introduction

Processor	MT7981B ARM Cotext-A53 dual-core CPU, 1.3GHZ main frequency
WIFI Chip	MT7976CN IEEE 802.11n/g/b/a/ac/ax, Max. 3000Mbps
RAM	DDR3 256MB
Flash	SPI NAND Flash 128MB
	EMMC 8GB (Choosable)

## 4.4 Hardware watchdog function introduction

This hardware product is designed with a hardware watchdog function. After the hardware watchdog is powered on, it will automatically start up and detect the heartbeat level output by the routing system that jumps once every second. If the routing system itself fails (such as a crash), it will also Naturally, the heartbeat level can no longer be output. At this time, if the hardware watchdog has not detected the heartbeat level within 120 seconds, it will shut down by itself for 15 seconds and then restart the entire system.

When the routing system is running normally, but the 5G module dialing is abnormal, the routing system will control the power supply of the 5G module through GPIO, so that the module will automatically restart to fix the 5G dialing abnormality.

Specific function of hardware watchdog	
Routing system exception	Module dialing exception
restart the whole system	Only restart the module